
Bulletin	1492-J, -W	1492-L
Type	Screw Type Terminal Blocks	Spring-Clamp Terminal Blocks
Technology	Screw terminations are a time-proven method of wire connection. Their greatest advantage is the ability to land multiple wires to a single terminal, potentially saving panel space. Screw type blocks can often accept up to five solid or stranded wires per terminal. They also typically provide the best visual indication of the wire connection.	Compared to screw type terminations, spring clamp terminations can be a significantly faster method of connection and can often reduce wire connection time by 30...50%. Because the wire is under constant tension from the spring clamp, spring type terminations also produce very favorable results in high vibration applications.
Certifications	UR, CSA	UR, CSA
Standards Compliance	IEC, CE	IEC, CE
Product Types	• Mini blocks • Feed-through blocks • Multi-conductor blocks • Plug-in style blocks • Grounding blocks • Fuse blocks • Two level terminal blocks • Three-Level Sensor blocks • Electrical Component blocks • Isolation blocks	• Mini blocks • Fuse blocks • Feed-through blocks • Grounding blocks • Multi-circuit blocks • Plug-in style blocks • Isolation blocks • Sensor blocks • Electrical component blocks
Product Selection	Page 12-6	Page 12-47

Certifications

Allen-Bradley terminal blocks generally have been designed to meet the requirements of one or more regulatory bodies. Most products have also been tested per additional standards. The following is a listing of some of the regulatory bodies and standards which apply to Allen-Bradley terminal block products. See the particular product description for information on specific certifications and ratings.



(Underwriters Laboratories) — Devices in this catalog with one of these ratings have been tested by Underwriters Laboratories and meet the requirements of one or more of the following United States Standards:

- UL 467 — Grounding and Bonding Equipment
- UL 486E — Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors
- UL 1059 — Standard for Terminal Blocks

Reference UL files E34648, E40735, E160646



(Underwriters Laboratories) — Devices in this catalog with this rating have been tested by Underwriters Laboratories and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference UL file E40735



(Canadian Standards Association) — Devices in this catalog with this rating have been tested by the Canadian Standards Association and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference CSA files LR67896



Terminal blocks listed in this catalog meet the requirements of the Low Voltage Directive put forth by the European Union. Devices have been tested and comply with one or more of the following European Norms:

- EN 60947-1 — Low Voltage Switchgear and Controlgear: General Rules
- EN 60947-7-1 — Low Voltage Switchgear and Controlgear: Terminal Blocks for Copper Conductors
- EN 60947-7-2 — Low Voltage Switchgear and Controlgear: Protective Conductor Terminal Blocks for Copper Conductors
- EN 60947-7-3 — Low Voltage Switchgear and Controlgear: Safety Requirements for Fuse Terminal Blocks



ATEX — Devices listed in this catalog with “ATEX” ratings meet the following European Norms per DEMKO or KEMA, Approval Certification Bodies for the European Union:

- EN 60079-7 — Electrical Apparatus for Potentially Explosive Atmospheres — General Requirements
- EN 60079-0 — Electrical Apparatus for Potentially Explosive Atmospheres — Increased Safety “e”

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.



Screw Connection Terminal Blocks

Certifications/Introduction

Ex e II — Many 1492-J, 1492-K, 1492-L, and 1492-W terminal blocks in this catalog meet the following Canadian Standards per Underwriters Laboratories:

CAN/CSA E 60079-7 — Electrical Apparatus for Explosive Atmospheres — Part 0 — General Requirements

CAN/CSA E 60079-0 — Electrical Apparatus for Explosive Atmospheres — Part 7 — Increased Safety “e”

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

AEx e II — Devices listed in this catalog with an “AEx e II” rating meet the following United States Standard per Underwriters Laboratories:

- ANSI/UL 60079-0 and 60079-7 — Standard for Electrical Equipment for Use in Class I, Zone 0, 1, and 2 Hazardous (Classified) Locations

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Rockwell Automation sales office or Allen-Bradley distributor for more information.

Lloyd's Register — Many 1492-H, 1492-J, 1492-L, and 1492-W terminal blocks in this catalog have been certified for use in marine, off-shore, and industrial installations per the following standard:

- Lloyd's Register Test Specification No. 1:1996

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.

The Allen-Bradley Line of IEC Terminal Blocks... International Products for a Worldwide Marketplace

The Allen-Bradley Bulletin 1492-J line of internationally approved IEC style terminal blocks offers a wide range of features and benefits ideally suited for many industrial applications. The 1492-J line has been designed to meet the tough requirements of almost every industrial application. Functional, internationally approved, finger-safe, and cost-effective — the Allen-Bradley Bulletin 1492-J line.

Products Available in the Bulletin 1492 Screw Terminal Block Line




Our family of IEC terminal blocks consists of many different types of blocks, from general feed-through terminal blocks for control wiring to specialty blocks for grounding and isolating. We even offer thermocouple terminal blocks, specifically designed for temperature-dependent process control applications.



Products offered within the Bulletin 1492 Screw Terminal Block line include:

- **Feed-Through Blocks**, capable of accommodating #30...2/0 AWG (0.2...70 mm²) wire
- **Grounding Blocks** for grounding a given circuit to the DIN Rail
- **Mini Blocks** for applications where panel space is at a premium
- **Two-Level Blocks** that double circuit wiring density
- **Multi-Conductor Blocks** that allow splitting or joining of control circuits
- **Three-Level Sensor Blocks** for coordination of three-wire sensor groups
- **Isolation Blocks** for circuit isolation during testing and troubleshooting
- **Fuse Blocks**, with and without blown fuse indication, for easily integrated overcurrent protection
- **Electrical Component Blocks** that allow the insertion of fixed components into control circuits. Available components include resistors, diodes, surge suppression circuits, and shunt bars.

Screw Connection Terminal Blocks

Mini Blocks


	1492-WM3				1492-WM4				1492-WMD1		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
	1.14\" (29 mm)				1.26\" (32 mm)				1.76\" (44.6 mm)		
Specifications	Single-circuit mini terminal block.				Single-circuit mini terminal block.				Two-circuit mini terminal block.		
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX		CSA	IEC
Voltage Rating	300V AC/DC	500V AC/DC	300V AC/DC	420V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC	420V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	15 A	24 A	15 A	24 A	20 A	32 A	20 A	32 A	15 A	15 A	17.5 A
Wire Range (Rated Cross Section)	#30...14 AWG	0.5...2.5 mm ²	#22...14 AWG	2.5 mm ²	#22...12 AWG	0.5...4.0 mm ²	#22...12 AWG	4.0 mm ²	#22...16 AWG		0.5...1.5 mm ²
Wire Strip Length	0.24 in. (6 mm)				0.39 in. (10 mm)				0.35 in. (9 mm)		
Recommended Tightening Torque	4.2...4.6 lb•in (0.47...0.52 N•m)				4.7...6.2 lb•in (0.53...0.70 N•m)				4.2...4.6 lb•in (0.47...0.52 N•m)		
Density	61 pcs/ft (200/m)				50 pcs/ft (166/m)				61 pcs/ft (200/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)		
Terminal Blocks		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color:	Grey	1492-WM3	50		1492-WM4	50		1492-WMD1	50		
	Red	1492-WM3-RE	50		1492-WM4-RE	50		1492-WMD1-RE	50		
	Blue	1492-WM3-B	50		1492-WM4-B	50		1492-WMD1-B	50		
	Black	1492-WM3-BL	50		1492-WM4-BL	50		1492-WMD1-BL	50		
	Green	1492-WM3-G	50		1492-WM4-G	50		1492-WMD1-G	50		
	Yellow	1492-WM3-Y	50		1492-WM4-Y	50		1492-WMD1-Y	50		
	Orange	1492-WM3-OR	50		1492-WM4-OR	50		1492-WMD1-OR	50		
	Brown	1492-WM3-BR	50		1492-WM4-BR	50		1492-WMD1-BR	50		
	White	1492-WM3-W	50		1492-WM4-W	50		1492-WMD1-W	50		
Accessories		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails: 1 m Sym. mini DIN (Steel)		1492-DR3	5		1492-DR3	5		1492-DR3	5		
End Barrier		1492-EBM3	50		1492-EBM4	50		1492-EBMD1	50		
End Anchors and Retainers: Mini Screwless End Retainer		1492-ERL15	20		1492-ERL15	20		1492-ERL15	20		
Mini DIN Anchor — Normal Duty		1492-EAJ15	50		1492-EAJ15	50		1492-EAJ15	50		
Jumpers: Insulated Side Jumper		1492-SJM5-10 (10-pole)	10		1492-N42 (2-pole) 1492-SJ6-10 (10-pole)	50 10		—	—		
Side Jumper — 12-pole uninsulated		—	—		—	—		1492-SJMD5-12 (Uninsulated)	10		
Center Jumper — 50-pole		—	—		1492-CJD6-50	5		—	—		
Center Jumper — 10-pole		1492-CJM5-10	10		1492-CJD6-10	10		—	—		
Center Jumper — 5-pole		—	—		1492-CJD6-5	10		—	—		
Center Jumper — 4-pole		—	—		1492-CJD6-4	10		—	—		
Center Jumper — 3-pole		1492-CJM5-3	10		1492-CJD6-3	10		—	—		
Center Jumper — 2-pole		1492-CJM5-2	10		1492-CJD6-2	10		—	—		
Center Jumper Link		1492-CJL5	10		1492-CJL6	10		—	—		
Other Accessories: Partition Plate		1492-PPM3	50		1492-PPM3	50		1492-PPMD1	50		
Test Plug		—	—		1492-TP28	10		—	—		
Test Plug Adapter		1492-TA285	10		1492-TA40	10		—	—		
Electrical Warning Plate (4-pole)		—	—		1492-EWP6-4	10		—	—		
Marking Systems: Snap-in Marker Card		1492-MS5X5 (80/card)	5		1492-MS6X9 (80/card)	5		1492-MS5X5 (80/card)	5		

	1492-WMG3		1492-WMG4	
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.				
Specifications	Single-circuit mini grounding terminal block.		Single-circuit mini grounding terminal block.	
Certifications	IEC			
Maximum Current	Grounding		Grounding	
Wire Range (Rated Cross Section)	#14 AWG (2.5 mm ²)		#22...12 AWG	0.5...4.0 mm ²
Wire Strip Length	0.31 in. (8 mm)		0.39 in. (10 mm)	
Recommended Tightening Torque	6.2 lb•in (0.7 N•m)		5.3 lb•in (0.6 N•m)	
Density	50 pcs/ft (166 pcs/m)		50 pcs/ft (166 pcs/m)	
Housing Temperature Range	—		-40...+195 °F (-40...+90 °C)	
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color: — Metallic	1492-WMG3	50	—	—
Green/Yellow	—	—	1492-WMG4	10
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails: 1 m Sym. Mini DIN (Steel)	1492-DR3	5	1492-DR3	5
End Anchors and Retainers: Mini Screwless End Retainer	—	—	1492-ERL15	20
Mini DIN Anchor — Normal Duty	—	—	1492-EAJ15	50
Other Accessories: Partition Plate	1492-PPM3	50	1492-PPM3	50
Marking Systems: Snap-in Marker Card	—	—	1492-MS6X9 (80/card)	5


Spring-Clamp Connection Terminal Blocks

Mini-Blocks with Center Jumper Option

1492-LMJ3



1492-LMJG3



Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.

Specifications

Mini rail-mount, feed-through terminal block with jumper capability

Mini rail-mount grounding terminal block

Certifications		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	600V AC/DC			500V AC/DC	275V AC/DC	—	—
Maximum Current	20 A			24 A	20 A	Grounding	
Wire Range (Rated Cross Section)	#26...12 AWG			2.5 mm²	#20...12 AWG	#26...12 AWG	2.5 mm²
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Color	Grey	1492-LMJ3		100	—		—
	Blue	1492-LMJ3-B		100	—		—
	Green/Yellow	—		—	1492-LMJG3		100
Accessories	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails 1 m Symmetrical DIN (Steel)	1492-DR3			5	1492-DR3		5
Screwless End Retainer	Grey	1492-ERL15		20	1492-ERL15		20
End Anchor	Grey	1492-EAJ15		50	1492-EAJ15		50
Jumpers	1492-CJLJ5-50			10	—		—
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-10			20	—		—
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-9			20	—		—
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-8			20	—		—
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-7			20	—		—
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-6			20	—		—
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-5			20	—		—
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-4			60	—		—
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-3			60	—		—
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-2			60	—		—
Plug-in Center Jumper — 2-Pole	1492-SJLM5-2			50	—		—
Side Jumper — 2-Pole	1492-TAL5-2			1	—		—
Side Jumper Installation Tool	1492-EBLMJ3			50	1492-EBLMJ3		50
End Barriers	Grey	1492-EBLMJ3-B		50	1492-EBLMJ3-B		50
	Blue	1492-EBLMJ3-Y		50	1492-EBLMJ3-Y		50
	Yellow	1492-EBLMJ3-Y		50	1492-EBLMJ3-Y		50
Marking Systems	1492-SM5X10 (144/card)			5	1492-SM5X10 (144/card)		5
Snap-in Marker Cards	1492-M5X5 (200/card)			5	1492-M5X5 (200/card)		5
Snap-In Marker Cards*	1492-MH5X10 (96/card)			5	1492-MH5X10 (96/card)		5
Hinged marker cards*							

* Markers can be installed over center jumper channel, with or without center jumper installed.

Spring-Clamp Connection Terminal Blocks

Mini-Blocks, Interlocking, 600V UL Rated

	1492-LM3			1492-LM3Q			1492-LMG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Mini rail-mount, feed-through terminal block			Mini rail-mount, feed-through terminal block with 2 connection points on each side			Mini rail-mount grounding terminal block		
Certifications									
Voltage Rating	600V AC/DC			600V AC/DC			—		
Maximum Current	20 A	25 A	24 A	20 A	25 A	24 A	Grounding		
Wire Range (Rated Cross Section)	#26...12 AWG 2.5 mm ²			#26...12 AWG 2.5 mm ²			#26...12 AWG 2.5 mm ²		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)			30 pcs/ft (99 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-LM3		100	1492-LM3Q		100	—	
	Blue	1492-LM3-B		100	1492-LM3Q-B		100	—	
	Green/Yellow	—		—	—		1492-LMG3	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails 1 m Symmetrical Mini DIN (Steel)	1492-DR3	5		1492-DR3	5		1492-DR3	5	
Screwless End Retainer	Grey	1492-ERL15		20	1492-ERL15		20	1492-ERL15	
End Anchor	Grey	1492-EAJ15		50	1492-EAJ15		50	1492-EAJ15	
Jumpers									
Side Jumper — 2-Pole		1492-SJLM5-2		50	1492-SJLM5-2		50	—	
Side Jumper Installation Tool		1492-TAL5-2		1	1492-TAL5-2		1	—	
End Barriers	Grey	1492-EBLM3		50	1492-EBLM3		50	1492-EBLM3	
	Blue	1492-EBLM3-B		50	1492-EBLM3-B		50	1492-EBLM3-B	
	Yellow	1492-EBLM3-Y		50	1492-EBLM3-Y		50	1492-EBLM3-Y	
Marking Systems									
Snap-In Marker Cards		1492-M5X10 (144/card)		5	1492-M5X10 (144/card)		5	1492-M5X10 (144/card)	
Snap-In Marker Cards		1492-M5X5 (200/card)		5	1492-M5X5 (200/card)		5	1492-M5X5 (200/card)	
Hinged Marker Cards		1492-MH5X10 (96/card)		5	1492-MH5X10 (96/card)		5	1492-MH5X10 (96/card)	

End Barriers, continued

Dimensions Width x Length x Height	For Use With	Color	Pkg Qty.	Cat. No.
0.20 x 0.94 x 1.31 in. (5.1 x 23.8 x 33.3 mm)	1492-LMP3, LMP3Q	Grey	50	1492-EBLMP3
		Blue	50	1492-EBLMP3-B
0.20 x 0.94 x 1.31 in. (5.1 x 23.8 x 33.3 mm)	1492-LM3, LM3Q, LMG3, LMP3E, LMP3QE	Grey	50	1492-EBLM3
		Blue	50	1492-EBLM3-B
		Yellow	50	1492-EBLM3-Y
0.06 x 0.97 x 1.38 in. (1.5 x 24.65 x 35 mm)	1492-LMJ3, LMJG3	Grey	50	1492-EBLMJ3
		Blue	50	1492-EBLMJ3-B
		Yellow	50	1492-EBLMJ3-Y
0.06 x 2.32 x 4.35 in. (1.5 x 59 x 110.5 mm)	1492-LTF3	Grey	20	1492-EBLTF3
0.06 x 2.69 x 1.77 in. (5 x 68.5 x 45 mm)	1492-LS2-3, LS2-3L, LSG2-3		50	1492-EBLS2-3
0.20 x 3.2 x 1.77 in. (5 x 81.5 x 45 mm)	1492-LS2-4, LS2-4L, LSG2-4		50	1492-EBLS2-4
0.06 x 1.81 x 3.74 in. (1.5 x 46 x 95 mm)	1492-LDAG3, LDG3P		20	1492-EBLDAG3
0.10 x 1.04 x 1.81 in. (2.5 x 26.4 x 46 mm)	1492-LC3		20	1492-EBLC3
0.10 x 1.65 x 2.72 in. (2.5 x 41.85 x 69 mm)	1492-LDC3		20	1492-EBLDC3
—	1492-LDG3ND, LD3N, LDG3N	Grey	20	1492-BSPJLD3N
—	1492-LDG3ND, LD3N, LDG3N	Blue	20	1492-BSPJLD3N-B

End Anchor/End Retainers

End anchors and end retainers mount at both ends of a group of terminal blocks to add rigidity to the terminal assembly and prevent sliding along the rails.

Photo	Dimensions Width x Length x Height	Tightening Torque	Markers	For Use With	Color	Pkg Qty.	Cat. No.
	0.31 x 2.20 x 1.85 in. (8 x 56 x 47 mm)	4.4 lb•in. (0.5 N•m)	1492-M7X12 1492-M8X5	199-DR1, 199-DR2, 1492-DR4, 1492-DR5, 1492-DR6, 1492-DR7, 1492-DR8, 1492-DR9	Grey	100	1492-EAJ35
	0.48 x 2.20 x 2.48 in. (12.2 x 56 x 63 mm)	4.4 lb•in. (0.5 N•m)	1492-M7X12 1492-M5X5	199-DR1, 199-DR2, 1492-DR4, 1492-DR5, 1492-DR6, 1492-DR7, 1492-DR8, 1492-DR9	Grey	50	1492-EAHJ35
	0.31 x 1.06 x 1.06 in. (8 x 27 x 27 mm)	3.5 lb•in. (0.9 N•m)	1492-M5X5	1492-DR3	Grey	50	1492-EAJ15
	0.24 x 2.19 x 1.63 in. (6 x 55.6 x 41.5 mm)	—	1492-M5X10 1492-M5X5	199-DR1, 199-DR2, 1492-DR4, 1492-DR5, 1492-DR6, 1492-DR7, 1492-DR8, 1492-DR9	Grey	20	1492-ERL35
	0.20 x 0.96 x 0.75 in. (5 x 24.5 x 19 mm)	—	1492-M5X10 1492-M5X5	1492-DR3	Grey	20	1492-ERL15