

|                                         |       |            |           |
|-----------------------------------------|-------|------------|-----------|
|                                         |       |            |           |
| Adjustable Lever<br>1.19...3 in. Radius | Nylon | 38.1 (1.5) | 802T-W17A |

| Type                                                                               | Roller Material                                  | Roller Diameter<br>[mm (in.)] | Roller Width<br>[mm (in.)] | Cat. No.   |           |
|------------------------------------------------------------------------------------|--------------------------------------------------|-------------------------------|----------------------------|------------|-----------|
|    | Nylon; L.H. roller on front; R.H. roller on back | 19.05 (0.75)                  | 7.11 (0.28)                | 802T-W4    |           |
|                                                                                    | Steel; L.H. roller on front; R.H. roller on back |                               | 6.35 (0.25)                | 802T-W4B   |           |
|                                                                                    | Nylon; Both rollers on front                     |                               | 7.11 (0.28)                | 802T-W4A   |           |
|                                                                                    | Nylon; Both rollers on rear                      |                               | 7.11 (0.28)                | 802T-NX115 |           |
|                                                                                    | Nylon; Both rollers on front                     |                               | 25.4 (1)                   | 802T-W4F   |           |
| Fork Lever<br>1.5 in. Radius                                                       | Steel; both rollers on front                     |                               | 6.35 (0.25)                | 802T-W4C   |           |
|                                                                                    | Nylon; L.H. roller on back; R.H. roller on front |                               | 7.11 (0.28)                | 802T-W4D   |           |
|   | Nylon R.H. adjustable                            | 19.05 (0.75)                  | 7.11 (0.28)                | 802T-W6    |           |
|                                                                                    | Steel R.H. adjustable                            |                               | 6.35 (0.25)                | 802T-W6A   |           |
|                                                                                    | Ball bearing R.H. Adj.                           |                               | 5.84 (0.23)                | 802T-W6B   |           |
|                                                                                    | Nylon L.H. Adj.                                  |                               | 7.11 (0.28)                | 802T-W6C   |           |
| Micrometer Adjustment<br>Lever\$<br>1.5 in. Radius                                 | Steel L.H. Adj.                                  |                               | 6.35 (0.25)                | 802T-W6D   |           |
|                                                                                    | Ball bearing L.H. Adj.                           |                               | 5.84 (0.23)                | 802T-W6E   |           |
|                                                                                    | Nylon R.H. Adj.                                  |                               | 25.4 (1)                   | 802T-W6F   |           |
|  | Nylon                                            | 19.05 (0.75)                  | 7.11 (0.28)                | ♣          | 802T-W7   |
|                                                                                    | Steel                                            |                               | 6.35 (0.25)                | ♣          | 802T-W7A  |
| Non-Adj. One-way Lever<br>1.5 in. Radius                                           | Ball bearing                                     |                               | 5.84 (0.23)                | ♣          | 802T-W7B  |
|  | Nylon                                            | 19.05 (0.75)                  | 7.11 (0.28)                | ‡          | 802T-W12  |
|                                                                                    | Steel                                            |                               | 6.35 (0.25)                | ‡          | 802T-W12A |
| Non-Adj. Offset Lever<br>1.44 in. Radius<br>Roller on Front                        | Ball bearing                                     |                               | 5.84 (0.23)                | 802T-W12B  |           |
|                                                                                    | Nylon                                            | 19.05 (0.75)                  | 7.11 (0.28)                | 802T-W12E  |           |