

802B Compact

Product Selection **Typical Wiring Diagram(s)** **Approximate Dimensions**



Rotary Arm



Center Rotary Arm



Wobble Stick

Head Type	Torque/Force to Operate, Max.	Travel to Operate Contacts, Max.	Reference Value		Output Type	Cat. No.	
			Maximum Travel	Travel to Reset Contacts, Max.		Pre-leaded	Quick-Disconnect ★
Rotary arm	0.216 N•m (2 lb•in.)	25°	70°	3°	Standard	802B-CSAAXSXC3	802B-CSAAXSXD4 802B-CSAAXSXR4
					AC LED	802B-CSAAXSLC3	802B-CSAAXSLR4
					DC LED	802B-CSDAXSLC3	802B-CSDAXSLD4
					Low Voltage/Current	802B-CSDAXSXC3	—
Center rotary arm	0.216 N•m (2 lb•in.)	10 ±3°	65°	4°	Standard	802B-CSAA2XSXC3	—
					AC LED	802B-CSAA2XSLC3	—
					DC LED	802B-CSDA2XSLC3	—
					Low Voltage/Current	802B-CSDA2XSXC3	—
Wobble stick	0.118 N•m (1.04 lb•in.)	15°	18° (Nominal Value)	11° (Nominal Value)	Standard	802B-CSACXSXC3	802B-CSACXSXD4 802B-CSACXSXR4
					AC LED	802B-CSACXSLC3	—
					DC LED	802B-CSDCXSLC3	—
					Low Voltage/Current	802B-CSDCXSXC3	—