





Slim Line Relays Type HK with Plug-in Quick Connect Terminations

	Wiring Diagrams (International)	Description	Contact Rating	Coil Voltage	Cat. No. ❶	PQ
	 Screw terminal socket 700-HN121	1 changeover contact - Contacts: bifurcated gold overlay, AgCdO	10 A	24 VAC	700-HKX6A24	1
				120 VAC	700-HKX6A1	
				24 VDC	700-HKX6Z24	
		1 changeover contact - Contacts: AgCdO	10 A	24 VAC	700-HK36A24	
				120 VAC	700-HK36A1	
				240 VAC	700-HK36A2	
				24 VDC	700-HK36Z24	
				110 VDC	700-HK36Z1	
	 Screw terminal socket 700-HN122	2 changeover contacts - Contacts: bifurcated gold overlay, AgCdO	5 A	24 VAC	700-HKX2A24	1
				120 VAC	700-HKX2A1	
				24 VDC	700-HKX2Z24	
		2 changeover contacts - Contacts: AgCdO	5 A	24 VAC	700-HK32A24	
				120 VAC	700-HK32A1	
				240 VAC	700-HK32A2	
				24 VDC	700-HK32Z24	
				110 VDC	700-HK32Z1	

❶ Pilot light option: Add suffix (-4) to the selected HC relay Cat. No.

PQ = Package Quantity

Accessories - Page 8-48
Specifications - Page 8-49
Dimensions - Page 8-50