

	Description	Pkg. Quantity	Cat. No.	
	Plastic mounting latch	10	800F-ALP	
	Mechanical interlock latch	1	*	800FC-ALP
	Replacement wire guide†	10	800FC-AWG	
	Replacement trim washer	10	800F-ATW1	
	Insulated side jumper	50	1492-SJ5A-24	
			1492-SJ5A-10	
	Hole plug	1	800F-N2	
	Contact block	10	Description	
			Type	
			N.O.	
			N.C.	
			N.O. low voltage — QuadCONNECT™	
			N.C. low voltage — QuadCONNECT™	
			N.C.E.B.	
			NOEM⚡	
			NOLM‡	
			NOEEM➤	
	Cable sleeve	1	3-hole (M20 x 1.5)	
			5-...9-hole (M32 x 1.5)	
	Protective boot	10	⚡	800F-ABE7
			⚡	800F-AUB2
	Narrow plastic guard	1	Yellow	
	Integrated LED module	10	§	800F-N3x
			§	800F-N5x

* Only for use with 1-, 2-, and 3-speed operators.

⚡ First contact closure of 1- and 2-speed operators.

‡ Second contact closure of 2-speed operators and third contact closure of 3-speed operators.

➤ First contact closure of 3-speed operators.

⚡ For proper operation, **Cat. No. 800F-X10M** must be mounted in position 3 of the mechanical or standard latch.

⚡ Not for use with 1-, 2-, and 3-speed operators.

§ To complete the cat. no., replace the x with one of the following letters for the desired color: **Y** = Amber, **R** = Red, **G** = Green, **B** = Blue, **W** = White.

† Wire guides are provided with enclosures.