




Screw Connection Terminal Blocks

Mini Blocks

	1492-WM3				1492-WM4				1492-WMD1		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
	1.14\" (29 mm)				1.26\" (32 mm)				1.76\" (44.6 mm)		
Specifications	Single-circuit mini terminal block.				Single-circuit mini terminal block.				Two-circuit mini terminal block.		
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX		CSA	IEC
Voltage Rating	300V AC/DC	500V AC/DC	300V AC/DC	420V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC	420V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	15 A	24 A	15 A	24 A	20 A	32 A	20 A	32 A	15 A	15 A	17.5 A
Wire Range (Rated Cross Section)	#30...14 AWG	0.5...2.5 mm ²	#22...14 AWG	2.5 mm ²	#22...12 AWG	0.5...4.0 mm ²	#22...12 AWG	4.0 mm ²	#22...16 AWG		0.5...1.5 mm ²
Wire Strip Length	0.24 in. (6 mm)				0.39 in. (10 mm)				0.35 in. (9 mm)		
Recommended Tightening Torque	4.2...4.6 lb•in (0.47...0.52 N•m)				4.7...6.2 lb•in (0.53...0.70 N•m)				4.2...4.6 lb•in (0.47...0.52 N•m)		
Density	61 pcs/ft (200/m)				50 pcs/ft (166/m)				61 pcs/ft (200/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)		
Terminal Blocks		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color:	Grey	1492-WM3	50			1492-WM4	50		1492-WMD1	50	
	Red	1492-WM3-RE	50			1492-WM4-RE	50		1492-WMD1-RE	50	
	Blue	1492-WM3-B	50			1492-WM4-B	50		1492-WMD1-B	50	
	Black	1492-WM3-BL	50			1492-WM4-BL	50		1492-WMD1-BL	50	
	Green	1492-WM3-G	50			1492-WM4-G	50		1492-WMD1-G	50	
	Yellow	1492-WM3-Y	50			1492-WM4-Y	50		1492-WMD1-Y	50	
	Orange	1492-WM3-OR	50			1492-WM4-OR	50		1492-WMD1-OR	50	
	Brown	1492-WM3-BR	50			1492-WM4-BR	50		1492-WMD1-BR	50	
	White	1492-WM3-W	50			1492-WM4-W	50		1492-WMD1-W	50	
Accessories		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails: 1 m Sym. mini DIN (Steel)		1492-DR3	5			1492-DR3	5		1492-DR3	5	
End Barrier		1492-EBM3	50			1492-EBM4	50		1492-EBMD1	50	
End Anchors and Retainers: Mini Screwless End Retainer		1492-ERL15	20			1492-ERL15	20		1492-ERL15	20	
Mini DIN Anchor — Normal Duty		1492-EAJ15	50			1492-EAJ15	50		1492-EAJ15	50	
Jumpers: Insulated Side Jumper		1492-SJM5-10 (10-pole)	10			1492-N42 (2-pole) 1492-SJ6-10 (10-pole)	50 10		—	—	
Side Jumper — 12-pole uninsulated		—	—			—	—		1492-SJMD5-12 (Uninsulated)	10	
Center Jumper — 50-pole		—	—			1492-CJD6-50	5		—	—	
Center Jumper — 10-pole		1492-CJM5-10	10			1492-CJD6-10	10		—	—	
Center Jumper — 5-pole		—	—			1492-CJD6-5	10		—	—	
Center Jumper — 4-pole		—	—			1492-CJD6-4	10		—	—	
Center Jumper — 3-pole		1492-CJM5-3	10			1492-CJD6-3	10		—	—	
Center Jumper — 2-pole		1492-CJM5-2	10			1492-CJD6-2	10		—	—	
Center Jumper Link		1492-CJL5	10			1492-CJL6	10		—	—	
Other Accessories: Partition Plate		1492-PPM3	50			1492-PPM3	50		1492-PPMD1	50	
Test Plug		—	—			1492-TP28	10		—	—	
Test Plug Adapter		1492-TA285	10			1492-TA40	10		—	—	
Electrical Warning Plate (4-pole)		—	—			1492-EWP6-4	10		—	—	
Marking Systems: Snap-in Marker Card		1492-MS5X5 (80/card)	5			1492-MS6X9 (80/card)	5		1492-MS5X5 (80/card)	5	

Screw Connection Terminal Blocks

Space-Saver Feed-Through Blocks




1492-W3

1492-W4

1492-W6

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Single-circuit terminal block.				Single-circuit terminal block.				Single-circuit terminal block.			
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX		IEC	CSA	ATEX
Voltage Rating	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	600V AC/DC	550V AC/DC
Maximum Current	20 A	24 A	20 A	24 A	30 A	32 A	30 A	32 A	40 A	41 A	40 A	41 A
Wire Range (Rated Cross Section)	#30...14 AWG	0.5...2.5 mm ²	#22...14 AWG	2.5 mm ²	#22...10 AWG	0.5...4.0 mm ²	#22...10 AWG	4.0 mm ²	#22...10 AWG	0.5...6.0 mm ²	#22...10 AWG	6.0 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.35 in. (9 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	5.0...5.6 lb•in (0.6 N•m)				5.0...5.6 lb•in (0.6 N•m)				5.6...6.8 lb•in (0.7 N•m)			
Density	61 pcs/ft (200 pcs/m)				50 pcs/ft (166 pcs/m)				43 pcs/ft (142 pcs/m)			
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)			
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color:	Grey	1492-W3		50	1492-W4			50	1492-W6			50
	Red	1492-W3-RE		50	1492-W4-RE			50	1492-W6-RE			50
	Blue	1492-W3-B		50	1492-W4-B			50	1492-W6-B			50
	Black	1492-W3-BL		50	1492-W4-BL			50	1492-W6-BL			50
	Green	1492-W3-G		50	1492-W4-G			50	1492-W6-G			50
	Yellow	1492-W3-Y		50	1492-W4-Y			50	1492-W6-Y			50
	Orange	1492-W3-OR		50	1492-W4-OR			50	1492-W6-OR			50
	Brown	1492-W3-BR		50	1492-W4-BR			50	1492-W6-BR			50
	White	1492-W3-W		50	1492-W4-W			50	1492-W6-W			50
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2
End Barrier	1492-EB3			50	1492-EB3			50	1492-EB10			50
End Anchors and Retainers:												
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50
Jumpers:					1492-N42 (2-pole)			50				
Insulated Side Jumper	1492-SJ5-10 (10-pole)			10	1492-SJ6-10 (10-pole)			10	—			—
Center Jumper — 50-pole	1492-CJ5-50			5	1492-CJ6-50			5	—			—
Center Jumper — 40-pole	—			—	—			—	1492-CJ7-40			5
Center Jumper — 10-pole	1492-CJ5-10			10	1492-CJ6-10			10	1492-CJ7-10			10
Center Jumper — 5-pole	1492-CJ5-5			10	1492-CJ6-5			10	1492-CJ7-5			10
Center Jumper — 4-pole	1492-CJ5-4			10	1492-CJ6-4			10	1492-CJ7-4			10
Center Jumper — 3-pole	1492-CJ5-3			10	1492-CJ6-3			10	1492-CJ7-3			10
Center Jumper — 2-pole	1492-CJ5-2			10	1492-CJ6-2			10	1492-CJ7-2			10
Center Jumper Link	1492-CJL5			10	1492-CJL6			10	1492-CJL7			10
Center Jumper Cover — White*	1492-CJCW5			20	1492-CJCW6			20	1492-CJCW6			20
Other Accessories:												
Partition Plate	1492-PP3			50	1492-PP3			50	1492-PP10			50
Separation Plate	1492-SP3			50	1492-SP3			50	—			—
Test Plug	—			—	1492-TP28			10	1492-TP28			10
Stackable Test Plug (with Legs)	—			—	1492-TP6EWL			10	—			—
Stackable Test Plug (without Legs)	—			—	1492-TP6E			10	—			—
Test Plug Adapter	1492-TA285			10	1492-TA40			10	1492-TA40			10
Electrical Warning Plate (1-pole)	1492-EWP5			10	1492-EWP6			10	1492-EWP7			10
Electrical Warning Plate (4-pole)	1492-EWP5-4			10	1492-EWP6-4			10	1492-EWP7-4			10
Marking Systems:												
Snap-in Marker Cards	1492-MS5X12 (80/card)			5	1492-MS6X12 (80/card)			5	1492-MS6X12 (80/card)			5

* May only be used as a marking surface. Cannot be installed over a center jumper.

IEC Terminal Block Accessories

Jumpers

Side Jumpers

For Use With	Pkg Qty.	Cat. No.
1492-WM4, W4	50	1492-N42
1492-H4, H5, H6, H7	10	1492-N49
	10	* 1492-SJS
1492-W3, WR3	10	1492-SJ5-10
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5A-10
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5A-24
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5B-24
1492-JD3, JD3C, JD3F, JDG3, JD3DF, JD3DR, JD3SS, JDG3P	50	1492-SJ5B-10
1492-WM4, W4, W4TW	10	⚡ 1492-SJ6-10
1492-JT3M	5	1492-SJ6A-50
1492-W10	10	1492-SJ8-10
1492-JD3FB, JDG3FB	50	1492-SJ8A-4
1492-JD3FB, JDG3FB	50	1492-SJ8A-3
1492-JD3FB, JDG3FB	50	1492-SJ8A-2
1492-LMP3, LMP3Q, LMJ3, LM3, LM3Q, LMP3E, LMP3QE	50	1492-SJLM5-2
1492-WMD1	10	‡ 1492-SJMD5-12
1492-WFB4, WFB424, WFB4250	10	1492-SJFB8-10
1492-WM3	10	1492-SJM5-10
1492-WTF3, WTS3, WTF3LP, WTS3LP, WTF3LN, WTS3LN	10	1492-SJT5-20-R
1492-WTF3, WTS3, WTF3LP, WTS3LP, WTF3LN, WTS3LN	10	1492-SJT5-20-B

Note: Side jumpers carry the same current rating as the terminal block used with it

* Side jumper insulating sleeve only for use with Cat. No. 1492-N49

⚡ Use jumper on single side of terminal block only

‡ Uninsulated

Two-Level Jumper

For Use With	Pkg Qty.	Cat. No.
1492-LTF3 (Connects Two Levels within a 1492-LTF3 Terminal Block)	20	1492-CJL5D