










Table 38 - Additional Accessories (Continued)

	Description		For Use With	Cat. No.
	Extension Shaft (Short length) • Cut to required length for mounting depth (front of DIN Rail to front of enclosure door) • For Cat. Nos. 140MT-C-DN66 and 140MT-C-DRY66 handles	3.2 cm (1.26 in.)	140MT (all) 140UT- D	140MT-C-DSS
	Extension Shaft (Standard length) • Cut to required length for mounting depth (front of DIN Rail to front of enclosure door) • For Cat. Nos. 140MT-C-DN66 and 140MT-C-DRY66 handles	26 cm (10.24 in.)		140MT-C-DS
	Extension Shaft (Extended length) • Cut to required length for mounting depth (front of DIN Rail to front of enclosure door) • For Cat. Nos. 140MT-C-DN66 and 140MT-C-DRY66 handles	41 cm (16.14 in.)		140MT-C-DSL
	Door Coupling Handle • Type 3, 3R, 4, 4X, 12 (IP66) • For up to 2 padlocks • Fits in 30.5 mm cutout • Requires 140MT-C-DNC coupler	Black	140MT (all) 140UT- D	140MT-SB
		Red/Yellow	140MT (all) 140UT- D	140MT-SY
	Extension Shaft • Cut to required length for mounting depth (front of DIN Rail to front of enclosure door)	12 in. (30.48 cm)	140MT-SB, 140MT-SY	140MT-S1
		21 in. (53.34 cm)	140MT-SB, 140MT-SY	140MT-S2
	Coupler • Included with Cat. Nos. 140MT-C-DN66 and 140MT-C-DRY66		140MT (all) 140UT- D	140MT-C-DNC
	Extension Shaft Support • Provides consistent alignment of the 140MT-C-DS and 140MT-C-DSL shafts with the 140MT-C-DN66 or 140MT-C-DRY66 door coupling handles • Recommended for shaft lengths >200 mm (7.9 in.) • Snaps on the right side of the 140MT-C, -D, -F, or 140UT-D device and allows the addition of one side-mounted auxiliary contact • Width: 9 mm (0.35 in.) • For use with screw-mounted or hat rail mounted devices		140MT (all) 140UT- D	140MT-C-SHS
	Legend Plate	Marking: "Hauptschalter" and "Main Switch"	140MT-C-DN66	140MT-C-DFCN
		Marking: "Not-Aus" and "Emergency Off"	140MT-C-DRY66	140MT-C-DFCRY
	Screw Adapter • For screw arrangement of a motor protection circuit breaker • Must be ordered in multiples of 10 (10 pieces/pkg)		140MT-C, D 140UT- D	140MT-C-N45
			140MT-F	140MT-F-N45