

## Spring-Clamp Connection Terminal Blocks



## Fuse Blocks

## 1492-RFB4...

## 1492-RAFB4...

Dimensions are not intended to be used for manufacturing purposes.

**Note:** Height dimension is measured from top of rail to top of terminal block.



| Specifications                      |  |  | Single-circuit fuse terminal block with or without blown fuse indicator |                             |                         | Single-circuit fuse terminal block with or without blown fuse indicator |                              |                         |
|-------------------------------------|--|--|-------------------------------------------------------------------------|-----------------------------|-------------------------|-------------------------------------------------------------------------|------------------------------|-------------------------|
| Certifications                      |  |  |                                                                         | cUR                         | IEC                     |                                                                         | cUR                          | IEC                     |
| Maximum Current                     |  |  | 15 A*                                                                   | 15 A*                       | 15 A*                   | 12 A                                                                    | 12 A                         | 12 A                    |
| Wire Range (Rated Cross Section)    |  |  | #22...12 AWG                                                            | #22...12 AWG                | 0.5...4 mm <sup>2</sup> | #22...12 AWG                                                            | #22...12 AWG                 | 0.5...4 mm <sup>2</sup> |
| Voltage Rating                      |  |  | RFB4/RAFB4                                                              | 300V AC/DC                  | 500V AC/DC              | RFB4/RAFB4                                                              | 300V AC/DC                   | 500V AC/DC              |
|                                     |  |  | RFB424/RAFB424                                                          | 10...57V AC/DC              |                         | RFB424/RAFB424                                                          | 10...57V AC/DC               |                         |
|                                     |  |  | RFB4250/RAFB4250                                                        | 85...264V AC                |                         | RFB4250/RAFB4250                                                        | 85...264V AC                 |                         |
| Indicator Type                      |  |  | RFB4/RAFB4                                                              | Non-indicating              |                         | RFB4/RAFB4                                                              | Non-indicating               |                         |
|                                     |  |  | RFB424/RAFB424                                                          | LED                         |                         | RFB424/RAFB424                                                          | LED                          |                         |
|                                     |  |  | RFB4250/RAFB4250                                                        | Neon                        |                         | RFB4250/RAFB4250                                                        | Neon                         |                         |
| Leakage Current                     |  |  | RFB4/RAFB4                                                              | —                           |                         | RFB4/RAFB4                                                              | —                            |                         |
|                                     |  |  | RFB424/RAFB424                                                          | 2 mA @ 24V                  |                         | RFB424/RAFB424                                                          | 2 mA @ 24V                   |                         |
|                                     |  |  | RFB4250/RAFB4250                                                        | 1 mA @ 264V                 |                         | RFB4250/RAFB4250                                                        | 1 mA @ 264V                  |                         |
| Fuse Size (Not Supplied)            |  |  |                                                                         | 5 x 20 mm                   |                         |                                                                         | 1/4 x 1 -1/4 in.             |                         |
| Wire Strip Length                   |  |  |                                                                         | 0.47 in. (12 mm)            |                         |                                                                         | 0.47 in. (12 mm)             |                         |
| Density                             |  |  |                                                                         | 37 pcs/ft (125 pcs/m)       |                         |                                                                         | 30 pcs/ft (100 pcs/m)        |                         |
| Insulation Temperature Range        |  |  |                                                                         | -4...+140 °F (-20...+60 °C) |                         |                                                                         | -4...+221 °F (-40...+105 °C) |                         |
| Terminal Blocks                     |  |  | Cat. No.                                                                | Pkg Qty.                    |                         | Cat. No.                                                                | Pkg Qty.                     |                         |
| Color                               |  |  | Black (Non-Indicating)                                                  | 1492-RFB4                   | 25                      | Black (Non-Indicating)                                                  | 1492-RAFB4                   | 25                      |
|                                     |  |  | Black (10...57V LED)                                                    | 1492-RFB424                 | 25                      | Black (10...57V LED)                                                    | 1492-RAFB424                 | 25                      |
|                                     |  |  | Black (85...264V Neon)                                                  | 1492-RFB4250                | 25                      | Black (85...264V Neon)                                                  | 1492-RAFB4250                | 25                      |
| Accessories                         |  |  | Cat. No.                                                                | Pkg Qty.                    |                         | Cat. No.                                                                | Pkg Qty.                     |                         |
| Mounting Rails                      |  |  |                                                                         |                             |                         |                                                                         |                              |                         |
| 1 m Symmetrical DIN (Steel)         |  |  | 199-DR1                                                                 | 10                          |                         | 199-DR1                                                                 | 10                           |                         |
| 1 m Symmetrical DIN (Aluminum)      |  |  | 1492-DR5                                                                | 10                          |                         | 1492-DR5                                                                | 10                           |                         |
| 1 m Hi-Rise Sym. DIN (Aluminum)     |  |  | 1492-DR6                                                                | 2                           |                         | 1492-DR6                                                                | 2                            |                         |
| 1 m Angled Hi-Rise Sym. DIN (Steel) |  |  | 1492-DR7                                                                | 2                           |                         | 1492-DR7                                                                | 2                            |                         |
| End Barrier                         |  |  | Not Required                                                            | —                           |                         | Not Required                                                            | —                            |                         |
| End Retainers/Anchors               |  |  |                                                                         |                             |                         |                                                                         |                              |                         |
| Screwless End Retainer              |  |  | 1492-ERL35                                                              | 20                          |                         | 1492-ERL35                                                              | 20                           |                         |
| DIN Rail — Heavy Duty               |  |  | 1492-EAHJ35                                                             | 50                          |                         | 1492-EAHJ35                                                             | 50                           |                         |
| Plug-in Center Jumper, 10-Pole      |  |  | 1492-CJR8-10                                                            | 10                          |                         | —                                                                       | —                            |                         |
| Plug-in Center Jumper, 9-Pole       |  |  | 1492-CJR8-9                                                             | 10                          |                         | —                                                                       | —                            |                         |
| Plug-in Center Jumper, 8-Pole       |  |  | 1492-CJR8-8                                                             | 10                          |                         | —                                                                       | —                            |                         |
| Plug-in Center Jumper, 7-Pole       |  |  | 1492-CJR8-7                                                             | 10                          |                         | —                                                                       | —                            |                         |
| Plug-in Center Jumper, 6-Pole       |  |  | 1492-CJR8-6                                                             | 10                          |                         | —                                                                       | —                            |                         |
| Plug-in Center Jumper, 5-Pole       |  |  | 1492-CJR8-5                                                             | 10                          |                         | 1492-CJRA10-5                                                           | 10                           |                         |
| Plug-in Center Jumper, 4-Pole       |  |  | 1492-CJR8-4                                                             | 10                          |                         | 1492-CJRA10-4                                                           | 10                           |                         |
| Plug-in Center Jumper, 3-Pole       |  |  | 1492-CJR8-3                                                             | 10                          |                         | 1492-CJRA10-3                                                           | 10                           |                         |
| Plug-in Center Jumper, 2-Pole       |  |  | 1492-CJR8-2                                                             | 10                          |                         | 1492-CJRA10-2                                                           | 10                           |                         |
| Center Jumper Link                  |  |  | 1492-CJRL6                                                              | 10                          |                         | 1492-CJRL5                                                              | 10                           |                         |
| Marking Systems                     |  |  |                                                                         |                             |                         |                                                                         |                              |                         |
| Snap-in Marker for Block            |  |  | 1492-MS8X12 (56/card)                                                   | 5                           |                         | 1492-MS8X12 (56/card)                                                   | 5                            |                         |
| Snap-in Marker for Handle           |  |  | 1492-MS6X9 (80/card)                                                    | 5                           |                         | 1492-MS6X9 (80/card)                                                    | 5                            |                         |

\* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.