

Data sheet | Item number: 790-108

Shield clamping saddle; 11 mm wide; 0-8 mm diameter conductors

www.wago.com/790-108



Data

Technical data

Main product function

Shield

Safety information 1

Note: Cannot be used for connecting ground conductors!

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.

Physical data

Width	11 mm / 0.433 inch
-------	--------------------

Material data

Weight	12 g
Material	Steel V2A Stainless steel

Commercial data

Product Group	2 (Terminal Block Accessories)
PU (SPU)	50 (10) Stück
Packaging type	box
Country of origin	DE
GTIN	4017332356954
Customs tariff number	8536904000

Optional accessories

Shield termination

Shield termination		
	Item no.: 790-112 Carrier with grounding foot; parallel to carrier rail; 25 mm long; Cu 10 mm x 3 mm	www.wago.com/790-112
	Item no.: 790-110 Carrier with grounding foot; parallel to carrier rail; 15 mm long; Cu 10 mm x 3 mm	www.wago.com/790-110
	Item no.: 790-115 Carrier with 2 grounding feet; parallel to carrier rail; 125 mm long; Cu 10 mm x 3 mm	www.wago.com/790-115
	Item no.: 790-113 Carrier with grounding foot; 90° to carrier rail; 45 mm long; Cu 10 mm x 3 mm	www.wago.com/790-113
	Item no.: 790-114 Carrier with grounding foot; parallel to carrier rail; 45 mm long; Cu 10 mm x 3 mm	www.wago.com/790-114

Mounting

Shield termination		
	Item no.: 790-101 Isolated mounting carrier; for busbar with sheet metal screw (3.5 x 9) mm	www.wago.com/790-101
	Item no.: 790-100	

Subject to changes. Please also observe the further product documentation!

Isolated mounting carrier; for busbar with screw M4 x 8 mm

www.wago.com/790-100**N-busbar**

Shield termination

**Item no.: 790-191**

U-shaped busbar; 100 mm wide; 60 mm high; Cu 10 mm x 3 mm

www.wago.com/790-191**Item no.: 790-190**

U-shaped busbar; 63 mm wide; 60 mm high; Cu 10 mm x 3 mm

www.wago.com/790-190**Item no.: 790-192**

U-shaped busbar; 63 mm wide; 35 mm high; Cu 10 mm x 3 mm

www.wago.com/790-192**Item no.: 790-193**

U-shaped busbar; 100 mm wide; 35 mm high; Cu 10 mm x 3 mm

www.wago.com/790-193

Mounting accessories

**Item no.: 210-133**

Busbar; tin-plated; 1000 mm long; Cu 10 mm x 3 mm

www.wago.com/210-133**Item no.: 790-133**

Busbar; tin-plated; 30 mm long; Cu 10 mm x 3 mm

www.wago.com/790-133**Item no.: 790-134**

Busbar; tin-plated; 50 mm long; Cu 10 mm x 3 mm

www.wago.com/790-134**Carrier rail**

Shield termination

**Item no.: 790-145**

Carrier rail; special perforations; 1000 mm long; tin-plated

www.wago.com/790-145**Downloads****Documentation****Bid Text**

790-108	Nov 28, 2018	doc	Download
doc - Datei		24.1 kB	
790-108	Feb 19, 2019	xml	Download
X81 - Datei		2.7 kB	

CAD files**CAD data**

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
 Germantown, WI 53022
 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
 Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
 We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



2D/3D Models 790-108	URL	Download
----------------------	---------------------	--------------------------

CAE data

WSCAD Universe 790-108	URL	Download
EPLAN Data Portal 790-108	URL	Download
ZUKEN Portal 790-108	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 790-108	URL	Download
Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm		

Installation Notes



Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



Installation

The shield clamping saddle is shipped ready for direct connection to the (10 x 3) mm busbar or to a drilled mounting plate. After connection, tighten the knurled screw to complete the installation.

Maximum tightening torque: 0.5 Nm



Removal

To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.



Carrier with grounding foot* (790-113), 45 mm long, busbar 90° to the DIN-rail

*for all shield clamping saddle sizes



Carrier with grounding foot* (790-114), 45 mm long, busbar parallel to the DIN-rail

*for all shield clamping saddle sizes



Carrier with grounding foot* (790-1145), 125 mm long, busbar parallel to the rail

*for all shield clamping saddle sizes

Subject to changes. Please also observe the further product documentation!



Securing an additional shield clamping saddle.




Tightening/removing a shield clamping saddle.




After connection, tighten the knurled screw to complete the installation.


Recommended tightening torque: 0.5 Nm




To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.



Carrier with grounding foot – busbar parallel to the rail



Insulated mounting carriers for a common shield reference potential, independent of housing potential



U-shaped (10 x 3) mm copper busbar

Subject to changes. Please also observe the further product documentation!



Snap shield clamping saddles into any metal plate (max. thickness: 3 mm).

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.