

		
Bulletin	1492-J, -W	1492-L
Type	Screw Type Terminal Blocks	Spring-Clamp Terminal Blocks
Technology	Screw terminations are a time-proven method of wire connection. Their greatest advantage is the ability to land multiple wires to a single terminal, potentially saving panel space. Screw type blocks can often accept up to five solid or stranded wires per terminal. They also typically provide the best visual indication of the wire connection.	Compared to screw type terminations, spring clamp terminations can be a significantly faster method of connection and can often reduce wire connection time by 30...50%. Because the wire is under constant tension from the spring clamp, spring type terminations also produce very favorable results in high vibration applications.
Certifications	UR, CSA	UR, CSA
Standards Compliance	IEC, CE	IEC, CE
Product Types	• Mini blocks • Feed-through blocks • Multi-conductor blocks • Plug-in style blocks • Grounding blocks • Fuse blocks • Two level terminal blocks • Three-Level Sensor blocks • Electrical Component blocks • Isolation blocks	• Mini blocks • Fuse blocks • Feed-through blocks • Grounding blocks • Multi-circuit blocks • Plug-in style blocks • Isolation blocks • Sensor blocks • Electrical component blocks
Product Selection	Page 12-6	Page 12-47

Certifications

Allen-Bradley terminal blocks generally have been designed to meet the requirements of one or more regulatory bodies. Most products have also been tested per additional standards. The following is a listing of some of the regulatory bodies and standards which apply to Allen-Bradley terminal block products. See the particular product description for information on specific certifications and ratings.



(Underwriters Laboratories) — Devices in this catalog with one of these ratings have been tested by Underwriters Laboratories and meet the requirements of one or more of the following United States Standards:

- UL 467 — Grounding and Bonding Equipment
- UL 486E — Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors
- UL 1059 — Standard for Terminal Blocks

Reference UL files E34648, E40735, E160646



(Underwriters Laboratories) — Devices in this catalog with this rating have been tested by Underwriters Laboratories and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference UL file E40735



(Canadian Standards Association) — Devices in this catalog with this rating have been tested by the Canadian Standards Association and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference CSA files LR67896



Terminal blocks listed in this catalog meet the requirements of the Low Voltage Directive put forth by the European Union. Devices have been tested and comply with one or more of the following European Norms:

- EN 60947-1 — Low Voltage Switchgear and Controlgear: General Rules
- EN 60947-7-1 — Low Voltage Switchgear and Controlgear: Terminal Blocks for Copper Conductors
- EN 60947-7-2 — Low Voltage Switchgear and Controlgear: Protective Conductor Terminal Blocks for Copper Conductors
- EN 60947-7-3 — Low Voltage Switchgear and Controlgear: Safety Requirements for Fuse Terminal Blocks



ATEX — Devices listed in this catalog with “ATEX” ratings meet the following European Norms per DEMKO or KEMA, Approval Certification Bodies for the European Union:

- EN 60079-7 — Electrical Apparatus for Potentially Explosive Atmospheres — General Requirements
- EN 60079-0 — Electrical Apparatus for Potentially Explosive Atmospheres — Increased Safety “e”

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.



Screw Connection Terminal Blocks

Certifications/Introduction

Ex e II — Many 1492-J, 1492-K, 1492-L, and 1492-W terminal blocks in this catalog meet the following Canadian Standards per Underwriters Laboratories:

CAN/CSA E 60079-7 — Electrical Apparatus for Explosive Atmospheres — Part 0 — General Requirements

CAN/CSA E 60079-0 — Electrical Apparatus for Explosive Atmospheres — Part 7 — Increased Safety “e”

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

AEx e II — Devices listed in this catalog with an “AEx e II” rating meet the following United States Standard per Underwriters Laboratories:

- ANSI/UL 60079-0 and 60079-7 — Standard for Electrical Equipment for Use in Class I, Zone 0, 1, and 2 Hazardous (Classified) Locations

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Rockwell Automation sales office or Allen-Bradley distributor for more information.

Lloyd's Register — Many 1492-H, 1492-J, 1492-L, and 1492-W terminal blocks in this catalog have been certified for use in marine, off-shore, and industrial installations per the following standard:

- Lloyd's Register Test Specification No. 1:1996

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.

The Allen-Bradley Line of IEC Terminal Blocks... International Products for a Worldwide Marketplace

The Allen-Bradley Bulletin 1492-J line of internationally approved IEC style terminal blocks offers a wide range of features and benefits ideally suited for many industrial applications. The 1492-J line has been designed to meet the tough requirements of almost every industrial application. Functional, internationally approved, finger-safe, and cost-effective — the Allen-Bradley Bulletin 1492-J line.

Products Available in the Bulletin 1492 Screw Terminal Block Line

Our family of IEC terminal blocks consists of many different types of blocks, from general feed-through terminal blocks for control wiring to specialty blocks for grounding and isolating. We even offer thermocouple terminal blocks, specifically designed for temperature-dependent process control applications.

Products offered within the Bulletin 1492 Screw Terminal Block line include:

- **Feed-Through Blocks**, capable of accommodating #30...2/0 AWG (0.2...70 mm²) wire
- **Grounding Blocks** for grounding a given circuit to the DIN Rail
- **Mini Blocks** for applications where panel space is at a premium
- **Two-Level Blocks** that double circuit wiring density
- **Multi-Conductor Blocks** that allow splitting or joining of control circuits
- **Three-Level Sensor Blocks** for coordination of three-wire sensor groups
- **Isolation Blocks** for circuit isolation during testing and troubleshooting
- **Fuse Blocks**, with and without blown fuse indication, for easily integrated overcurrent protection
- **Electrical Component Blocks** that allow the insertion of fixed components into control circuits. Available components include resistors, diodes, surge suppression circuits, and shunt bars.

Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L6				1492-L6T				1492-L10				
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.													
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block				
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX	
Voltage Rating	600V AC/DC			800V AC/DC	600V AC/DC			800V AC/DC	600V AC/DC			800V AC/DC	
Maximum Current	50 A			41 A	50 A			41 A	60 A			55 A	
Wire Range (Rated Cross Section)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...8 AWG)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	#16...6 AWG		10 mm ²	10 mm ² (16...8 AWG)	
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				0.70 in. (18 mm)				
Density	37 pcs/ft (123 pcs/m)				37 pcs/ft(123 pcs/m)				30 pcs/ft (99 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating	See page 12-78												
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	
Color	Grey			1492-L6	50	1492-L6T			50	1492-L10			25
	Red			1492-L6-RE	50	1492-L6T-RE			50	1492-L10-RE			25
	Blue			1492-L6-B	50	1492-L6T-B			50	1492-L10-B			25
	Black			1492-L6-BL	50	1492-L6T-BL			50	1492-L10-BL			25
	Green			1492-L6-G	50	1492-L6T-G			50	1492-L10-G			25
	Yellow			1492-L6-Y	50	1492-L6T-Y			50	1492-L10-Y			25
	Orange			1492-L6-OR	50	1492-L6T-OR			50	1492-L10-OR			25
	Brown			1492-L6-BR	50	1492-L6T-BR			50	1492-L10-BR			25
	White			1492-L6-W	50	1492-L6T-W			50	1492-L10-W			25
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	
Mounting Rails													
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10	
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2	
End Barriers	Grey	1492-EBL6		50	1492-EBL6T	50		1492-EBL10	20				
	Blue	1492-EBL6-B		50	1492-EBL6T-B	50		1492-EBL10-B	20				
	Yellow	1492-EBL6-Y		50	1492-EBL6T-Y	50		1492-EBL10-Y	20				
End Anchors and Retainers													
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20	
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100	
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50	
Jumpers													
Plug-in Center Jumper — 32-Pole	1492-CJL8-32			10	1492-CJL8-32			10	—			—	
Plug-in Center Jumper — 4-Pole	1492-CJL8-4			60	1492-CJL8-4			60	—			—	
Plug-in Center Jumper — 3-Pole	1492-CJL8-3			60	1492-CJL8-3			60	—			—	
Plug-in Center Jumper — 2-Pole	1492-CJL8-2			60	1492-CJL8-2			60	1492-CJL10-2			25	
Other Accessories													
Test Plug	—			—	—			—	1492-TP23			20	
Test Plug (Stackable)	1492-TPL8			25	1492-TPL8			25	—			—	
Electrical Warning Plate	1492-EWPL8			20	1492-EWPL8			20	1492-EWPL10			20	
Marking Systems													
Snap-In Marker Cards*	1492-M6X12 (120/card)			5	1492-M6X12 (120/card)			5	1492-M6X12 (120/card)			5	
Snap-In Marker Cards	1492-MR8X12 (84/card)			5	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5	
Hinged Marker Cards	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5	1492-MH5X15 (96/card)			5	

* May only be mounted in terminal block corner marking positions.

Screwless Center Jumpers



For Use With	Color	Pkg Qty.	Cat. No.
1492-L2..., L2T, L2Q, LD2, LD2C	Yellow	60	1492-CJL4-2
		60	1492-CJL4-3
		60	1492-CJL4-4
		60	1492-CJL4-5
		20	1492-CJL4-10
1492-LM3, LC3, LDC3, LDAG3, LDG3P, JKD3..., J3P..., J3, J3TW (see Note)	Yellow	60	1492-CJLJ5-2
	Red	60	1492-CJLJ5-2-R
	Blue	60	1492-CJLJ5-2-B
	Black	60	1492-CJLJ5-2-BL
	Yellow	60	1492-CJLJ5-3
	Red	60	1492-CJLJ5-3-R
	Blue	60	1492-CJLJ5-3-B
	Black	60	1492-CJLJ5-3-BL
	Yellow	60	1492-CJLJ5-4
		20	1492-CJLJ5-5
		20	1492-CJLJ5-6
		20	1492-CJLJ5-7
		20	1492-CJLJ5-8
		20	1492-CJLJ5-9
		20	1492-CJLJ5-10
	Red	20	1492-CJLJ5-10-R
	Blue	20	1492-CJLJ5-10-B
	Black	20	1492-CJLJ5-10-BL
	White	20	1492-CJLJ5-10-W
	Yellow	10	1492-CJLJ5-50
	Red	10	1492-CJLJ5-50-R
	Blue	10	1492-CJLJ5-50-B
	Black	10	1492-CJLJ5-50-BL
	White	10	1492-CJLJ5-50-W

For Use With	Pkg Qty.	Cat. No.
1492-RFB4	10	1492-CJR8-2
	10	1492-CJR8-3
	10	1492-CJR8-4
	10	1492-CJR8-5
	10	1492-CJR8-6
	10	1492-CJR8-7
	10	1492-CJR8-8
	10	1492-CJR8-9
	10	1492-CJR8-10
	10	1492-CJRA10-2
1492-RAFB4	10	1492-CJRA10-3
	10	1492-CJRA10-4
	10	1492-CJRA10-5

For Use With	Color	Pkg Qty.	Cat. No.
1492-J4, J4M (see Note)	Yellow	60	1492-CJLJ6-2
	Red	60	1492-CJLJ6-2-R
	Blue	60	1492-CJLJ6-2-B
	Black	60	1492-CJLJ6-2-BL
	Yellow	60	1492-CJLJ6-3
	Red	60	1492-CJLJ6-3-R
	Blue	60	1492-CJLJ6-3-B
	Black	60	1492-CJLJ6-3-BL
	Yellow	60	1492-CJLJ6-4
	Yellow	20	1492-CJLJ6-10
	Red	20	1492-CJLJ6-10-R
	Blue	20	1492-CJLJ6-10-B
	Black	20	1492-CJLJ6-10-BL
	Yellow	10	1492-CJLJ6-41
	Red	10	1492-CJLJ6-41-R
	Blue	10	1492-CJLJ6-41-B
	Black	10	1492-CJLJ6-41-BL
1492-L6, L6T, L16D	Yellow	60	1492-CJL8-2
		60	1492-CJL8-3
		60	1492-CJL8-4
		10	1492-CJL8-32
1492-L10	Yellow	25	1492-CJL10-2
1492-L16	Yellow	25	1492-CJL12-2
1492-L35	Yellow	10	1492-CJL16-2
1492-L3, L3T, L3Q, L3P, LD3, LD3C, LKD3, LTF3, LS2..., L16D	Yellow	60	1492-CJK5-2
		60	1492-CJK5-3
		60	1492-CJK5-4
		20	1492-CJK5-5
		20	1492-CJK5-6
		20	1492-CJK5-7
		20	1492-CJK5-8
		20	1492-CJK5-9
		20	1492-CJK5-10
		10	1492-CJK5-50
		60	1492-CJK6-2
1492-L4, L4T, L4Q, LD4DF, LD4DR, LD4SS, LD4, LD4C, L16D	Yellow	60	1492-CJK6-3
		60	1492-CJK6-4
		20	1492-CJK6-5
		20	1492-CJK6-6
		20	1492-CJK6-7
		20	1492-CJK6-8
		20	1492-CJK6-9
		20	1492-CJK6-10
		20	1492-CJK6-20