

# NEMA/EEMAC Terminal Blocks

## Open Construction Blocks, Continued

	<b>1492-CA3</b>	<b>1492-CD3</b>	<b>1492-CD8</b>				
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.							
<b>Specifications</b>	<i>Terminal block, screw terminal with #6 screw.</i>	<i>Terminal block, screw terminal with #8 screw.</i>	<i>Terminal block, screw terminal with wire clamp.</i>				
Approvals							
Voltage Rating	600V AC/DC	600V AC/DC	600V AC/DC				
Maximum Current	20 A	35 A	35 A				
Wire Range (Rated Cross Section)	#22...#14 AWG (0.5...2.5 mm <sup>2</sup> )	#22...#10 AWG (0.5...6 mm <sup>2</sup> )	#22...#10 AWG (0.5...6 mm <sup>2</sup> )				
Wire Strip Length	Prepared Conductors Only	Prepared Conductors Only	0.38" (9.7 mm)				
Recommended Tightening Torque	12 lb-in. (1.4 Nm)	10...16 lb-in. (1.1...1.8 Nm)	10...16 lb-in. (1.1...1.8 Nm)				
Density	30 pcs./ft (98/m)	22 pcs./ft (72/m)	22 pcs./ft (72/m)				
Insulation Temperature Range	-40...+221°F (-40...+105°C)	-40...+221°F (-40...+105°C)	-40...+221°F (-40...+105°C)				
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	
Color:	White	1492-CA3	50	1492-CD3	50	1492-CD8	50
	Two 3' Rails White	1492-CA3175 (88/Rail)	1	1492-CD3130 (65/Rail)	1	1492-CD8130 (65/Rail)	1
	Gold	1492-CA3GL	50	1492-CD3GL	50	1492-CD8GL	50
	Red	1492-CA3RE	50	1492-CD3RE	50	1492-CD8RE	50
	Blue	1492-CA3B	50	1492-CD3B	50	1492-CD8B	50
	Black	1492-CA3BL	50	1492-CD3BL	50	1492-CD8BL	50
	Green	1492-CA3G	50	1492-CD3G	50	1492-CD8G	50
	Yellow	1492-CA3Y	50	1492-CD3Y	50	1492-CD8Y	50
	Brown	1492-CA3BR	50	1492-CD3BR	50	1492-CD8BR	50
	Violet	1492-CA3VT	50	1492-CD3VT	50	1492-CD8VT	50
	Gray	1492-CA3GY	50	1492-CD3GY	50	1492-CD8GY	50
	Orange	1492-CA3OR	50	1492-CD3OR	50	1492-CD8OR	50
<b>Accessories</b> (page 185)	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	
Mounting Rails:							
3' Scored A-B Rail	1492-N1	20	1492-N1	20	1492-N1	20	
3' Rigid A-B Rail	1492-N22	20	1492-N22	20	1492-N22	20	
3' High Rise A-B Rail	1492-N44	2	1492-N44	2	1492-N44	2	
Standoff Brackets (Use Every 12")	1492-N25	2	1492-N25	2	1492-N25	2	
End Barrier	1492-N16	50	1492-N16	50	1492-N16	50	
End Anchors:							
A-B Rail — Heavy Duty	1492-N23	10	1492-N23	10	1492-N23	10	
A-B Rail — Snap On	1492-N47	50	1492-N47	50	1492-N47	50	
A-B Rail-Retaining Clip-Light Duty	1492-N2	50	1492-N2	50	1492-N2	50	
Jumpers:							
2-pole Uninsulated	1492-N14	50	1492-N15	50	1492-N15	50	
50-pole Uninsulated	—	—	—	—	—	—	
Marking Systems	1492-N8	25	1492-N8	25	1492-N8	25	

Prepared conductors utilize ring, spade, or hook connectors.