

Code (See page 2-112)	Approx. Dimensions [mm (in.)]	Safedge Profile	Description	Cushion Factor	Length [m (ft)]	Cat. No.
I, L		0210S	Black, EPDM, with Sealing Lip, Weight: 1291 g/m (0.87 lbs/ft)	41 mm (1.61 in.)	5 (16.4)	440F-E0210S05
					10 (32.8)	440F-E0210S10
					20 (65.6)	440F-E0210S20
M		0118S	Black, EPDM, Weight: 242 g/m (0.163 lbs/ft) (mini profile)	3.75 mm (0.15 in.)	5 (16.4)	440F-E0118S05
					10 (32.8)	440F-E0118S10
					20 (65.6)	440F-E0118S20
N, O		1111S	Black, EPDM, Weight: 680 g/m (0.457 lbs/ft)	NA	5 (16.4)	440F-E1111S05
					10 (32.8)	440F-E1111S10
					20 (65.6)	440F-E1111S20

Note: Maximum roll size before axial connector needed is 20 m (65.6 ft).

Product Selection—C-Rails

Code	Approx. Dimension [mm (in.)]	Description	Cat. No.
A		Aluminium type, Type C112/A. Suitable for all profiles. Length: 3 m (9.8 ft) Weight: 258 g/m (0.17 lbs/ft)	440F-R1212
B		Zinc-Coated Steel; Type C112/S. Suitable for all profiles. Length: 2 m (6.5 ft) Weight: 663 g/m (0.45 lbs/ft)	440F-R1112
C		PVC Black; Type C112/PB. Suitable for all profiles. Length: 3 m (9.8 ft) Weight: 111 g/m (0.07 lbs/ft)	440F-R1212PB
D		PVC Red; Type C112/PR. Suitable for all profiles. Length: 3 m (9.8 ft) Weight: 111 g/m (0.07 lbs/ft)	440F-R1212PR
E		PVC Yellow; Type C112/PY. Suitable for all profiles. Length: 3 m (9.8 ft) Weight: 111 g/m (0.07 lbs/ft)	440F-R1212PY
F		Aluminium Vertical Lip; Type C112/A2. Suitable for all profiles. Length: 2 m (6.5 ft) Weight: 368 g/m (0.25 lbs/ft)	440F-R1214
G		Aluminium Horizontal Lip; Type C112/A3. Suitable for all profiles. Length: 2 m (6.5 ft) Weight: 388 g/m (0.26 lbs/ft)	440F-R1215
H		Aluminium Deep Channel; Type C112/A4. Suitable for all profiles. Length: 2 m (6.5 ft) Weight: 345 g/m (0.23 lbs/ft)	440F-R1216
I		Aluminium; Suitable for Mini Profile Only. Length: 2 m (6.5 ft) Weight: 150 g/m (0.10 lbs/ft)	440F-R1219

2-Safety Edges