

Table 2 - 1411-8xxx Accuracy

Cat. No.	Current Ratio	VA for $\pm 1\%$ Class	ANSI Metering Class at 60 Hz					Secondary Winding Resistance (ohms at 75 °C)	Continuous Thermal Rating Factor	
			B0.1	B0.2	B0.5	B0.9	B1.8		at 30 °C	at 55 °C
1411-8 ⁽¹⁾ -201	200:5	5.0	1.2	1.2	2.4	4.8	4.8	0.030	2.0	2.0
1411-8 ⁽¹⁾ -251	250:5 *	7.5	0.6	0.6	1.2	2.4	4.8	0.044	2.0	2.0
1411-8 ⁽¹⁾ -301	300:5 *	15.0	0.6	0.6	1.2	2.4	2.4	0.049	2.0	2.0
1411-8 ⁽¹⁾ -401	400:5 *	25.0	0.3	0.3	0.6	1.2	2.4	0.079	2.0	1.5
1411-8 ⁽¹⁾ -501	500:5 *	35.0	0.3	0.3	0.6	0.6	1.2	0.102	2.0	1.5
1411-8 ⁽¹⁾ -601	600:5 *	50.0	0.3	0.3	0.6	0.6	1.2	0.147	1.5	1.33
1411-8 ⁽¹⁾ -751	750:5 *	50.0	0.3	0.3	0.6	0.6	1.2	0.184	1.5	1.0
1411-8 ⁽¹⁾ -801	800:5 *	60.0	0.3	0.3	0.3	0.6	0.6	0.197	1.5	1.0
1411-8 ⁽¹⁾ -102	1000:5 *	75.0	0.3	0.3	0.3	0.6	0.6	0.246	1.33	1.0
1411-8 ⁽¹⁾ -122	1200:5 *	75.0	0.3	0.3	0.3	0.3	0.6	0.169	1.5	1.0
1411-8 ⁽¹⁾ -152	1500:5 *	90.0	0.3	0.3	0.3	0.3	0.6	0.316	1.33	1.0
1411-8 ⁽¹⁾ -162	1600:5 *	100.0	0.3	0.3	0.3	0.3	0.6	0.337	1.33	0.8
1411-8 ⁽¹⁾ -202	2000:5 *	120.0	0.3	0.3	0.3	0.3	-	0.422	1.0	0.8
1411-8 ⁽¹⁾ -252	2500:5 *	50.0	0.3	0.3	0.3	0.3	-	0.438	1.0	0.8
1411-8 ⁽¹⁾ -302	3000:5	60.0	0.3	0.3	0.3	0.3	-	0.526	1.0	0.8
1411-8 ⁽¹⁾ -322	3200:5	70.0	0.3	0.3	0.3	0.3	-	0.561	1.0	0.8
1411-8 ⁽¹⁾ -402	4000:5	80.0	0.3	0.3	0.3	0.3	-	0.973	0.8	0.6

(1) When ordering, prefix catalog number with model designation required, for example, 1411-8SHT-201 or 1411-8RL-301.

1411-8xxx Dimensions and Accuracy

Figure 2 - 1411-8xxx Dimensions

