

Table 5 - 1411-180 Accuracy

Cat. No.	Current Ratio	VA for $\pm 1\%$ Class	ANSI Metering Class at 60 Hz					Secondary Winding Resistance (ohms at 75 °C)	Continuous Thermal Rating	
			B0.1	B0.2	B0.5	B0.9	B1.8		at 30 °C	at 55 °C
1411 - 180 ⁽¹⁾ -500	50:5	1.5	2.4	-	-	-	-	0.009	1.33	1.0
1411 - 180 ⁽¹⁾ -750	75:5	2.5	1.2	2.4	-	-	-	0.018	1.33	1.0
1411 - 180 ⁽¹⁾ -101	100:5	2.5	1.2	2.4	4.8	-	-	0.021	1.33	1.0
1411 - 180 ⁽¹⁾ -151	150:5 ⁽²⁾	5.0	0.6	1.2	2.4	4.8	-	0.038	1.33	1.0
1411 - 180 ⁽¹⁾ -201	200:5 ⁽²⁾	12.5	0.6	0.6	1.2	2.4	-	0.051	1.33	1.0
1411 - 180 ⁽¹⁾ -251	250:5 ⁽²⁾	12.5	0.3	0.3	0.6	1.2	-	0.064	1.33	1.0
1411 - 180 ⁽¹⁾ -301	300:5 ⁽²⁾	25.0	0.3	0.3	0.6	1.2	2.4	0.076	1.33	1.0
1411 - 180 ⁽¹⁾ -401	400:5 ⁽²⁾	50.0	0.3	0.3	0.3	0.6	1.2	0.102	1.33	1.0
1411 - 180 ⁽¹⁾ -501	500:5 ⁽²⁾	50.0	0.3	0.3	0.3	0.6	1.2	0.148	1.33	1.0
1411 - 180 ⁽¹⁾ -601	600:5 ⁽²⁾	50.0	0.3	0.3	0.3	0.6	1.2	0.177	1.33	1.0
1411 - 180 ⁽¹⁾ -751	750:5 ⁽²⁾	50.0	0.3	0.3	0.3	0.6	1.2	0.174	1.33	1.0
1411 - 180 ⁽¹⁾ -801	800:5 ⁽²⁾	75.0	0.3	0.3	0.3	0.6	1.2	0.202	1.33	1.0
1411 - 180 ⁽¹⁾ -102	1000:5 ⁽²⁾	100.0	0.3	0.3	0.3	0.3	0.6	0.253	1.33	1.0
1411 - 180 ⁽¹⁾ -122	1200:5 ⁽²⁾	125.0	0.3	0.3	0.3	0.3	0.3	0.303	1.33	1.0
1411 - 180 ⁽¹⁾ -152	1500:5 ⁽²⁾	160.0	0.3	0.3	0.3	0.3	0.3	0.307	1.33	1.0
1411 - 180 ⁽¹⁾ -162	1600:5 ⁽²⁾	175.0	0.3	0.3	0.3	0.3	0.3	0.359	1.25	1.0
1411 - 180 ⁽¹⁾ -202	2000:5 ⁽²⁾	200.0	0.3	0.3	0.3	0.3	0.3	0.449	1.0	0.75

(1) When ordering, prefix catalog number with model designation required, for example, 1411-180RL-301 or 1411-180SHT-301.

(2) Approved for revenue metering by Industry Canada. No. T-189

1411-180 Dimensions and Accuracy

Figure 5 - 1411-180 Dimensions

