




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L2				1492-L2T				1492-L2Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block with 2 connection points per side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	300V AC/DC		500V AC/DC	550V AC/DC	300V AC/DC		500V AC/DC	550V AC/DC	300V AC/DC		500V AC/DC	550V AC/DC
Maximum Current	15 A	20 A	17.5 A	15 A	15 A	20 A	17.5 A	15 A	15 A	20 A	17.5 A	15 A
Wire Range (Rated Cross Section)	#26...14 AWG		1.5 mm ²	1.5 mm ²	#26...14 AWG		1.5 mm ²	1.5 mm ²	#26...14 AWG		1.5 mm ²	1.5 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)				87 pcs/ft (285 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color	Grey	1492-L2	50		1492-L2T	50			1492-L2Q	50		
	Red	1492-L2-RE	50		1492-L2T-RE	50			1492-L2Q-RE	50		
	Blue	1492-L2-B	50		1492-L2T-B	50			1492-L2Q-B	50		
	Black	1492-L2-BL	50		1492-L2T-BL	50			1492-L2Q-BL	50		
	Green	1492-L2-G	50		1492-L2T-G	50			1492-L2Q-G	50		
	Yellow	1492-L2-Y	50		1492-L2T-Y	50			1492-L2Q-Y	50		
	Orange	1492-L2-OR	50		1492-L2T-OR	50			1492-L2Q-OR	50		
	Brown	1492-L2-BR	50		1492-L2T-BR	50			1492-L2Q-BR	50		
	White	1492-L2-W	50		1492-L2T-W	50			1492-L2Q-W	50		
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails												
1 m Symmetrical DIN (Steel)	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Aluminum)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barriers	Grey	1492-EBL2	50		1492-EBL2T	50			1492-EBL2Q	50		
	Blue	1492-EBL2-B	50		1492-EBL2T-B	50			1492-EBL2Q-B	50		
	Yellow	1492-EBL2-Y	50		1492-EBL2T-Y	50			1492-EBL2Q-Y	50		
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
DIN Rail — Normal Duty	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Jumpers												
Plug-in Center Jumper — 10-Pole	1492-CJL4-10		20		1492-CJL4-10		20		1492-CJL4-10		20	
Plug-in Center Jumper — 5-Pole	1492-CJL4-5		60		1492-CJL4-5		60		1492-CJL4-5		60	
Plug-in Center Jumper — 4-Pole	1492-CJL4-4		60		1492-CJL4-4		60		1492-CJL4-4		60	
Plug-in Center Jumper — 3-Pole	1492-CJL4-3		60		1492-CJL4-3		60		1492-CJL4-3		60	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2		60		1492-CJL4-2		60		1492-CJL4-2		60	
Other Accessories												
Reducing Sleeves #28...#24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2		100		1492-PSL2-2		100		1492-PSL2-2		100	
Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey	1492-PSL2-5		100		1492-PSL2-5		100		1492-PSL2-5		100	
Test Plug (Stackable)	1492-TPL4		25		1492-TPL4		25		1492-TPL4		25	
Electrical Warning Plate	1492-EWPL4		20		1492-EWPL4		20		1492-EWPL4		20	
Marking Systems												
Snap-In Marker Cards	1492-M3X12 (120/card)		5		1492-M3X12 (120/card)		5		1492-M3X12 (120/card)		5	
Snap-In Marker Cards	1492-M3X5 (100/card)		5		1492-M3X5 (100/card)		5		1492-M3X5 (100/card)		5	