




1492-HM1

1492-HM2

1492-HM3

Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.							
Specifications		Finger-Safe terminal block, single-circuit, multi-rail mount.		Finger-Safe terminal block, two-circuit, multi-rail mount.		Finger-Safe terminal block, single-circuit, multi-rail mount.	
Approvals		UL / CSA / IEC		UL / CSA / IEC		UL / CSA / IEC	
Voltage Rating		600V AC/DC		600V AC/DC		600V AC/DC	
Maximum Current		30 A		24 A [IEC: 30 A]		55 A [IEC: 57 A]	
Wire Range (Rated Cross Section)		#30...#12 AWG (0.05...4 mm ²)		#30...#12 AWG (0.05...4 mm ²)		#22...#8 AWG (0.5...10 mm ²)	
Wire Strip Length		0.38" (9.7 mm)		0.38" (9.7 mm)		0.38" (9.7 mm)	
Recommended Tightening Torque		3...7 lb-in. (0.3...0.8 Nm)		3...7 lb-in. (0.3...0.8 Nm)		8...16 lb-in. (0.9...1.8 Nm)	
Density		50 pcs./ft (164/m)		50 pcs./ft (164/m)		37 pcs./ft (123/m)	
Insulation Temperature Range		-40...+221°F (-40...+105°C)		-40...+221°F (-40...+105°C)		-40...+221°F (-40...+105°C)	
Terminal Blocks		Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.
Color:	White	1492-HM1	80	1492-HM2	50	1492-HM3	50
	Gold	1492-HM1GL	80	1492-HM2GL	50	—	—
	Red	1492-HM1RE	80	1492-HM2RE	50	1492-HM3RE	50
	Blue	1492-HM1B	80	1492-HM2B	50	1492-HM3B	50
	Black	1492-HM1BL	80	1492-HM2BL	50	1492-HM3BL	50
	Green	1492-HM1G	80	1492-HM2G	50	1492-HM3G	50
	Yellow	1492-HM1Y	80	1492-HM2Y	50	1492-HM3Y	50
	Brown	1492-HM1BR	80	1492-HM2BR	50	1492-HM3BR	50
	Violet	1492-HM1VT	80	1492-HM2VT	50	1492-HM3VT	50
	Gray	1492-HM1GY	80	1492-HM2GY	50	1492-HM3GY	50
	Orange	1492-HM1OR	80	1492-HM2OR	50	1492-HM3OR	50
Accessories (page 0-185)		Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.
Mounting Rails:							
3' Scored A-B Rail		1492-N1	20	1492-N1	20	1492-N1	20
3' Rigid A-B Rail		1492-N22	20	1492-N22	20	1492-N22	20
3' High Rise A-B Rail		1492-N44	2	—	—	1492-N44	2
Standoff Brackets (use every 12")		1492-N25	2	1492-N25	2	1492-N25	2
1 m Symmetrical DIN		199-DR1	10	199-DR1	10	199-DR1	5
1 m Symmetrical DIN (alumin.)		1492-DR5	10	1492-DR5	10	1492-DR5	5
1 m Hi-Rise Symmetrical DIN		1492-DR6	2	1492-DR6	2	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN		1492-DR7	2	1492-DR7	2	1492-DR7	2
End Barrier		1492-NM36	50	1492-NM40	50	1492-NM36	50
End Anchors:							
A-B Rail — Heavy Duty		1492-N23	10	1492-N23	10	1492-N23	10
A-B Rail — Normal Duty		1492-N47	50	—	—	1492-N47	50
A-B Rail — Retaining Clip — Light Duty		1492-N2	50	—	—	—	—
DIN Rail — Normal Duty		1492-EA35	50	1492-EA35	50	1492-EA35	50
DIN Rail — Heavy Duty		1492-EAH35	50	1492-EAH35	50	1492-EAH35	50
Side Jumpers:							
2-pole Uninsulated		1492-N42	50	1492-N42	50	—	—
10-pole Insulated		1492-SJ6-10	10	1492-SJ6-10	10	1492-SJ8-10	5
50-pole Uninsulated		1492-N39	10	1492-N39	10	—	—
Side Jumper Insulating Sleeve		1492-SJS	10	1492-SJS	10	—	—
Marking Systems		1492-SMN81	5	1492-SMN81	5	1492-SMN81	5