



|                      |                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                         |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      |                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                      |
| Bulletin             | 1492-J, -W                                                                                                                                                                                                                                                                                                                                                       | 1492-L                                                                                                                                                                                                                                                                                                                                  |
| Type                 | <b>Screw Type Terminal Blocks</b>                                                                                                                                                                                                                                                                                                                                | <b>Spring-Clamp Terminal Blocks</b>                                                                                                                                                                                                                                                                                                     |
| Technology           | Screw terminations are a time-proven method of wire connection. Their greatest advantage is the ability to land multiple wires to a single terminal, potentially saving panel space. Screw type blocks can often accept up to five solid or stranded wires per terminal. They also typically provide the best visual indication of the wire connection.          | Compared to screw type terminations, spring clamp terminations can be a significantly faster method of connection and can often reduce wire connection time by 30...50%. Because the wire is under constant tension from the spring clamp, spring type terminations also produce very favorable results in high vibration applications. |
| Certifications       | UR, CSA                                                                                                                                                                                                                                                                                                                                                          | UR, CSA                                                                                                                                                                                                                                                                                                                                 |
| Standards Compliance | IEC, CE                                                                                                                                                                                                                                                                                                                                                          | IEC, CE                                                                                                                                                                                                                                                                                                                                 |
| Product Types        | <ul style="list-style-type: none"> <li>• Mini blocks</li> <li>• Feed-through blocks</li> <li>• Multi-conductor blocks</li> <li>• Plug-in style blocks</li> <li>• Grounding blocks</li> <li>• Fuse blocks</li> <li>• Two level terminal blocks</li> <li>• Three-Level Sensor blocks</li> <li>• Electrical Component blocks</li> <li>• Isolation blocks</li> </ul> | <ul style="list-style-type: none"> <li>• Mini blocks</li> <li>• Fuse blocks</li> <li>• Feed-through blocks</li> <li>• Grounding blocks</li> <li>• Multi-circuit blocks</li> <li>• Plug-in style blocks</li> <li>• Isolation blocks</li> <li>• Sensor blocks</li> <li>• Electrical component blocks</li> </ul>                           |
| Product Selection    | Page 12-6                                                                                                                                                                                                                                                                                                                                                        | Page 12-47                                                                                                                                                                                                                                                                                                                              |

## Certifications

Allen-Bradley terminal blocks generally have been designed to meet the requirements of one or more regulatory bodies. Most products have also been tested per additional standards. The following is a listing of some of the regulatory bodies and standards which apply to Allen-Bradley terminal block products. See the particular product description for information on specific certifications and ratings.



(Underwriters Laboratories) — Devices in this catalog with one of these ratings have been tested by Underwriters Laboratories and meet the requirements of one or more of the following United States Standards:

- UL 467 — Grounding and Bonding Equipment
- UL 486E — Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors
- UL 1059 — Standard for Terminal Blocks

Reference UL files E34648, E40735, E160646



(Underwriters Laboratories) — Devices in this catalog with this rating have been tested by Underwriters Laboratories and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference UL file E40735



(Canadian Standards Association) — Devices in this catalog with this rating have been tested by the Canadian Standards Association and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference CSA files LR67896



Terminal blocks listed in this catalog meet the requirements of the Low Voltage Directive put forth by the European Union. Devices have been tested and comply with one or more of the following European Norms:

- EN 60947-1 — Low Voltage Switchgear and Controlgear: General Rules
- EN 60947-7-1 — Low Voltage Switchgear and Controlgear: Terminal Blocks for Copper Conductors
- EN 60947-7-2 — Low Voltage Switchgear and Controlgear: Protective Conductor Terminal Blocks for Copper Conductors
- EN 60947-7-3 — Low Voltage Switchgear and Controlgear: Safety Requirements for Fuse Terminal Blocks



**ATEX** — Devices listed in this catalog with “ATEX” ratings meet the following European Norms per DEMKO or KEMA, Approval Certification Bodies for the European Union:

- EN 60079-7 — Electrical Apparatus for Potentially Explosive Atmospheres — General Requirements
- EN 60079-0 — Electrical Apparatus for Potentially Explosive Atmospheres — Increased Safety “e”

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.



## Screw Connection Terminal Blocks

### Certifications/Introduction

**Ex e II** — Many 1492-J, 1492-K, 1492-L, and 1492-W terminal blocks in this catalog meet the following Canadian Standards per Underwriters Laboratories:

CAN/CSA E 60079-7 — Electrical Apparatus for Explosive Atmospheres — Part 0 — General Requirements

CAN/CSA E 60079-0 — Electrical Apparatus for Explosive Atmospheres — Part 7 — Increased Safety “e”

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

**AEx e II** — Devices listed in this catalog with an “AEx e II” rating meet the following United States Standard per Underwriters Laboratories:

- ANSI/UL 60079-0 and 60079-7 — Standard for Electrical Equipment for Use in Class I, Zone 0, 1, and 2 Hazardous (Classified) Locations

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Rockwell Automation sales office or Allen-Bradley distributor for more information.

**Lloyd's Register** — Many 1492-H, 1492-J, 1492-L, and 1492-W terminal blocks in this catalog have been certified for use in marine, off-shore, and industrial installations per the following standard:

- Lloyd's Register Test Specification No. 1:1996

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.

### The Allen-Bradley Line of IEC Terminal Blocks... International Products for a Worldwide Marketplace

The Allen-Bradley Bulletin 1492-J line of internationally approved IEC style terminal blocks offers a wide range of features and benefits ideally suited for many industrial applications. The 1492-J line has been designed to meet the tough requirements of almost every industrial application. Functional, internationally approved, finger-safe, and cost-effective — the Allen-Bradley Bulletin 1492-J line.

### Products Available in the Bulletin 1492 Screw Terminal Block Line

Our family of IEC terminal blocks consists of many different types of blocks, from general feed-through terminal blocks for control wiring to specialty blocks for grounding and isolating. We even offer thermocouple terminal blocks, specifically designed for temperature-dependent process control applications.

Products offered within the Bulletin 1492 Screw Terminal Block line include:

- **Feed-Through Blocks**, capable of accommodating #30...2/0 AWG (0.2...70 mm<sup>2</sup>) wire
- **Grounding Blocks** for grounding a given circuit to the DIN Rail
- **Mini Blocks** for applications where panel space is at a premium
- **Two-Level Blocks** that double circuit wiring density
- **Multi-Conductor Blocks** that allow splitting or joining of control circuits
- **Three-Level Sensor Blocks** for coordination of three-wire sensor groups
- **Isolation Blocks** for circuit isolation during testing and troubleshooting
- **Fuse Blocks**, with and without blown fuse indication, for easily integrated overcurrent protection
- **Electrical Component Blocks** that allow the insertion of fixed components into control circuits. Available components include resistors, diodes, surge suppression circuits, and shunt bars.


## Screw Connection Terminal Blocks

## Specialty Feed-Through Blocks

## 1492-J4CTB

Dimensions are not intended to be used for manufacturing purposes.

**Note:** Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Single-level feed through block with circuit-break test/measurement plug capability

|                                  |                                 |            |                         |
|----------------------------------|---------------------------------|------------|-------------------------|
| Certifications                   | <b>UL</b>                       | <b>CSA</b> | <b>IEC</b>              |
| Voltage Rating                   | 300V AC/DC                      |            | 500V AC/DC              |
| Maximum Current                  | 8 A                             |            | 6 A                     |
| Wire Range (Rated Cross Section) | #26...10 AWG                    |            | 0.5...4 mm <sup>2</sup> |
| Wire Strip Length                | 0.394 in. (10 mm)               |            |                         |
| Recommended Tightening Torque    | 4.4...7.1 lb•in (0.5...0.8 N•m) |            |                         |
| Density                          | 49 pcs/ft (163 pcs/m)           |            |                         |
| Housing Temperature Range        | -58...+248 °F (-50...+120 °C)   |            |                         |
| Short-Circuit Current Rating     | See page 12-42                  |            |                         |

**Terminal Blocks****Cat. No.****Pkg Qty.**

|        |      |            |    |
|--------|------|------------|----|
| Color: | Grey | 1492-J4CTB | 50 |
|--------|------|------------|----|

**Accessories****Cat. No.****Pkg Qty.**

|                                     |                              |              |     |
|-------------------------------------|------------------------------|--------------|-----|
| Mounting Rails:                     |                              |              |     |
| 1 m Symmetrical DIN (Steel)         | <b>199-DR1</b>               |              | 10  |
| 1 m Symmetrical DIN (Aluminum)      | <b>1492-DR5</b>              |              | 10  |
| 1 m Hi-Rise Sym. DIN (Aluminum)     | <b>1492-DR6</b>              |              | 2   |
| 1 m Angled Hi-Rise Sym. DIN (Steel) | <b>1492-DR7</b>              |              | 2   |
| End Barrier                         | Grey                         | 1492-EBJ4CTB | 50  |
| End Anchors:                        |                              |              |     |
| Screwless End Retainer              | <b>1492-ERL35</b>            |              | 20  |
| DIN Rail - Normal Duty              | <b>1492-EAJ35</b>            |              | 100 |
| DIN Rail - Heavy Duty               | <b>1492-EAHJ35</b>           |              | 50  |
| Other Accessories:                  |                              |              |     |
| Test Plug - Make Before Break       | 1492-TPCMB                   |              | 25  |
| Test Plug - Break Before Make       | 1492-TPCBM                   |              | 25  |
| Marking Systems:                    |                              |              |     |
| Snap-in marker cards                | <b>1492-MR6X8</b> (120/card) |              | 5   |
| Snap-in marker cards                | <b>1492-M6X5</b> (200/card)  |              | 5   |