

IP66	Use With Switch	Number of Contacts*	ABS	Required Shaft	Noryl Material	Required Shaft
			Cat. No.	Cat. No.	Cat. No.	Cat. No.
	194L-A12/16	1...2	194L-G3572	194L-G3195	194L-G3576	194L-G3195
		3...4	194L-G3572	194L-G2830	194L-G3576	194L-G2830
		5...6	194L-G3573	194L-G3195	194L-G3577	194L-G3195
	194L-A20/25	1...2	194L-G3572	194L-G3194	194L-G3576	194L-G3194
		3...4	194L-G3572	194L-G2830	194L-G3576	194L-G2830
		5...6	194L-G3573	194L-G3194	194L-G3577	194L-G3194
	194L-E12/16	1...4	* 194L-G3574	194L-G3380	194L-G3578*	194L-G3380
		5...8	* 194L-G3575	194L-G3380	194L-G3579*	194L-G3380
	194L-E20/25	1...4	* 194L-G3574	194L-G3380	194L-G3578*	194L-G3380
		5...8	* 194L-G3575	194L-G3380	194L-G3579*	194L-G3380

Use With Size 6 Handles

- * Covers must be drilled for operating handle by user. Does not include earth/ground — neutral terminal.
* Refer to the switching diagrams that follow to determine the number of switch contacts.

2

	Description	Pkg. Qty.	Cat. No.
	Metal Shaft Extension with Padlock Provision ON Switch in OFF Position L = 110...235 mm (4-21/64....9-1/4 in.)	1	194L-G3393
	Metal Shaft Extension with Padlock Provision ON Switch in OFF Position L = 230...350 mm (9-3/64....13-51/64 in.)	1	194L-G3394
	Metal Shaft Extension For modification of Cat. No. 194L-G3393/ G3394 when used with any switches other than 2-position, 90° rotation.	10	194L-G3399
	Standard Interlock Shaft For Use With 194L-A12...40 = 44 mm (1-47/64 in.)	5	194L-G2830*
	Interlock Shaft For Use With 194L-A12...40 = 52 mm (2-3/64 in.)		194L-G3194*
	Interlock Shaft For Use With 194L-A12...40 = 57 mm (2-15/64 in.)		194L-G3195*
	Shaft Extension Including Coupling For Use With 194L-A12...40 = 24 mm (15/16 in.)	10	194L-G2853
	Standard Shaft For Use With 194L-E12...40 = 34 mm (1-11/32 in.)	5	194L-G3380

- * For Use With **194L-A...** Base-Mounted switches only.