




Spring-Clamp Connection Terminal Blocks

Grounding Blocks

	1492-LG16				1492-LG35				1492-LDG2		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block				Two-circuit terminal block with 1 feed-through and 1 ground circuit		
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	—	—	—	—	—	—	—	—	300V AC/DC	500V AC/DC	—
Maximum Current	Grounding				Grounding				10 A	17.5 A	—
Wire Range (Rated Cross Section)	#14...6 AWG	#14...4 AWG	16 mm ²	16 mm ² (16...6 AWG)	#12...2 AWG	35 mm ²	35 mm ² (#14...2 AWG)	—	#28...16 AWG	1.5 mm ²	—
Wire Strip Length	0.70 in. (18 mm)				0.98 in. (25 mm)				0.31 in. (8 mm)		
Density	25 pcs/ft (82 pcs/m)				18 pcs/ft (62 pcs/m)				87 pcs/ft (285 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		
Color: Green/Yellow	1492-LG16			25	1492-LG35			10	—		
Grey	—			—	—			—	1492-LDG2		
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1		
1 m Symmetrical Heavy Duty DIN (Steel, Unslotted)	199-DR4			5	199-DR4			5	199-DR4		
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5		
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6		
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7		
1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	1492-DR8			5	1492-DR8			5	1492-DR8		
1 m Symmetrical Heavy Duty DIN (Steel)	1492-DR9			5	1492-DR9			5	1492-DR9		
End Barrier Yellow	1492-EBL16-Y			20	Integrated			—	—		
Grey	—			—	—			—	1492-EBLD2		
End Anchors and Retainers	1492-ERL35			20	1492-ERL35			20	1492-ERL35		
Screwless End Retainer	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35		
DIN Rail — Normal Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35		
DIN Rail — Heavy Duty	—			—	—			—	1492-PSL2-2		
Other Accessories:											
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²) White	—			—	—			—	1492-PSL2-5		
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	—			—	—			—	—		
Test Plug	1492-TP23			20	1492-TP23			20	1492-TPL4		
Electrical Warning Plate	—			—	—			—	1492-EWPL4		
Marking Systems:	1492-M7X12 (108/card)			5	1492-M7X12 (108/card)			5	1492-M3X12 (120/card)		
Snap-In Marker Cards*	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5	1492-M3X5 (100/card)		
Hinged Marker Cards	1492-MH5X15 (96/card)			5	1492-MH5X10 (96/card)			—	—		

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Short-Circuit Current Ratings

Short-Circuit Current Ratings — Fuse Ratings

Cat. No.	Wire Cu [AWG]		Overcurrent Protection Fuse Required Class/Max. Amp Rating						Maximum Voltage	SCCR, RMS SYM [A]
	Line	Load	J	T	RK1	RK5	G	CC		
1492-L3	14...12	14...12	30	30	—	—	30	30	600	100,000
1492-L3Q										
1492-L3T										
1492-LD3										
1492-L3QS										
1492-LMJ3										
1492-LMJG3										
1492-LKD3										
1492-L3P										
1492-LG3T										
1492-LG3Q										
1492-LG3										
1492-LD3C										
1492-LDG3C										
1492-LDG3										
1492-LC3	14...12	14...12	30	30	—	—	30	30	300	100,000
1492-LDC3										
1492-LDG3P										
1492-LDG3ND										
1492-LDG3N										
1492-LD3N										
1492-LD31P										
1492-LD3Q2P										
1492-LG31P										
1492-LG3T1P										
1492-L3T1P										
1492-LDG3FB										
1492-L4	14...10	14...10	60	60	30	—	30	30	600	100,000
1492-L4Q										
1492-L4T										
1492-LD4										
1492-LD4C										
1492-LG4										
1492-LG4T										
1492-LG4Q										
1492-LD4DFX2										
1492-L6	14...8	14...8	60	60	30	—	60	30	600	100,000
1492-L6T										
1492-LG6										
1492-LG6T	14...8	14...8	60	60	30	—	60	30	300	100,000
1492-LAFB6	14...8	14...8	60	60	30	—	60	30	300	100,000
1492-L10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-LG10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-L16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-LG16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-L35	12...2	12...2	200	200	100	30	60	30	600	100,000
1492-LG35	12...2	12...2	200	200	100	30	60	30	600	100,000

